



MIX-SF FRONTAL MIXING BUCKET SAFE DISCHARGE



PATENTED



HB400



GEARBOX TRANSMISSION DELIVERS HIGH PERFORMANCE AND DOES NOT REQUIRE CONTINUOUS MAINTENANCE INTERVENTIONS. THE USE OF DUAL CROSS RELIEF AND FLOW DIVIDER VALVES GRANTS EFFECTIVENESS AND RELIABILITY EVEN IN THE MOST DIFFICULT WORK CONDITIONS.



STANDARD TECHNICAL FEATURES

1 SAFE LOCKING/DISCHARGE (PATENTED)

THE OPERATOR LOCKS THE DISCHARGE PIPE FROM THE BUCKET'S SIDE IN THE SAFEST WORK CONDITION.

2 CONTROL ROD FOR THE DISCHARGE PIPE

IT ENABLES THE PIPE'S DISPLACEMENT FOR THE SIDE POURING.

3 AUGER REMOVAL

THE BUCKET'S BODY HAS BEEN DESIGNED IN A SUCH WAY THAT THE ENTIRE AUGER CAN BE REMOVED THUS MAKING THE MAINTENANCE OPERATION EASIER.

4 GEARMOTOR

IT GUARANTEES HIGH PERFORMANCES TO THE ENTIRE SYSTEM.

5 ELECTRIC KIT

IT ALLOWS THE CONTROL BOTH OF THE MIXING AND THE DISCHARGE OPERATIONS FROM THE CAB.



OPTIONAL


6 ARTICULATED LOADERS, BACKHOE LOADERS AND TELEHANDLER HANDLERS HITCH

IT'S POSSIBLE TO ADD THE HITCH FOR ARTICULATED LOADERS, BACKHOE LOADERS AND TELEHANDLER HANDLERS TO THE SKID LOADER HITCH PROVIDED WITH THE STANDARD EQUIPMENT.

7 FLOWRATE REDUCERS

COMPULSORY FOR MACHINES WITH OILFLOW EXCEEDING THE REQUIRED ONE

8 14 (A) OR 8 PIN (B) CONNECT



	MOD.	MIX 150SF.2	MIX 200SF.2	MIX 250SF.2	MIX 350SF.2	MIX 450SF.2	MIX 600SF.2	MIX 800SF.2	MIX 1000SF.2	MIX 1200SF.2
A MM (IN)		1000 (39)	1100 (43)	1350 (53)	1350 (53)	1670 (66)	1750 (69)	1830 (72)	2000 (79)	2000 (79)
B MM (IN)		1265 (49,8)	1360 (53,5)	1610 (63,3)	1630 (64)	1946 (77)	2018 (79)	2230 (87,7)	2440 (96)	2440 (96)
C MM (IN)		620 (24)	650 (26)	650 (26)	720 (28)	720 (28)	835 (33)	910 (36)	990 (39)	1100 (43)
D MM (IN)		530 (21)	580 (23)	610 (24)	680 (27)	680 (27)	800 (31)	840 (33)	910 (36)	980 (39)
W/O COUPLER	KG (LB)	260 (573)	315 (694)	350 (771)	370 (816)	425 (937)	555 (1223)	675 (1488)	850 (1874)	905 (1995)
WITH COUPLER	KG (LB)	600 (1323)	775 (1708)	925 (2039)	1175 (2590)	1460 (3219)	1930 (4254)	2515 (5545)	3150 (6944)	3665 (8080)
DISCHARGE PIPE	L (GAL)	150 (39,6)	200 (52,8)	250 (66)	350 (92,5)	450 (118,9)	600 (158,5)	800 (211,3)	1000 (264,2)	1200 (317)
MAX	L/MIN (GAL/MIN)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	100 (26)
MAX	BAR (PSI)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)